

What is the installation process?

Pangaea floor is installed in a 4 stage process. First there is a pour, containing the mix of base colours and aggregate(s) to a 12-15mm height. Then there is a 3 pass grind/grout/polish process, which will bring the finish product to a 10-12mm finish. We can supply you with our installation manual for further details.

Are topical sealers used?

Yes.

For residential installations we recommend Lithofin Stain Stop Plus or Mitec 104 Colour Enhance. For Commercial installation we recommend Glazer, Flimstar and Armaplate. Although Pangaea is mechanically polished so it will not wear off, we recommend every 2-3 years a clean and buff re-application of the penetrating sealer to prolong the lustre and life of the product.

What is the Care and Maintenance procedure?

Pangaea is very similar to any high end polished surface. It is important that the floor is only cleaned with Pangaea recommended cleaners. Up keep is minimal and can be part of the cleaning regime. For all Care and Maintenance information please contact us for further details.

Will Pangaea stain?

Pangaea is stain resistant with the Pangaea sealer or coating system. Harsh chemicals such as acidic, alkaline, and oil based products require Pangaea to be cleaned immediately to avoid staining the surface.

Can Pangaea be installed over timber or stone?

Due to the make up of Pangaea we can bond to any surface. As long as the pre-existing substrate is structural, we can install over it.

Will Pangaea crack?

It is important to note Pangaea is dimensionally stable. It will however crack if there is sufficient movement in the substrate (surface) that it is laid on. It is important that the subfloor be structurally stable or be treated prior to installation as required.

Can Pangaea be repaired?

Yes.

Pangaea is repairable and can be virtually invisibly mended if required due to unforeseen circumstances.

How close to edges can Pangaea go?

As Pangaea is a liquid-applied material all cabinetry, furniture, skirting, kitchen, kickers etc should be removed prior to installation. Due to the limitations of grinding/polishing equipment a 5mm edge tape is installed against all vertical surfaces.

Will there be dust?

Contractors will endeavour to minimise dust. However due to the nature of the initial polishing process, some dust is inevitable.



What will the finish look like?

As per all natural products, there may be some slight imperfections noticed under close scrutiny such as uneven aggregate, hairline scratches, pin-holes, entrapped air mixes. These are considered part of the products character and design, which makes every Pangaea floor uniquely attractive and desirable. Please contact Pangaea representatives for samples which are indicative of the finish.

Can Pangaea be used for stairs, tables or bench tops?

Absolutely. Pangaea is flexible and can be installed in various ways. Depending on its exact location, different sealers may be used.

Can you install Pangaea to shower basins or externally?

No. We do not recommend these areas for installation.

If you have other questions please contact Pangaea Australia for assistance and we would be glad to answer them for you.

Pangaea Australia Pty Ltd
ABN 63 643 368 323
www.pangaeafloors.com.au
info@pangaeafloors.com.au
Ph: +61 468 777 181